

## Double-Ended Cylinders

**Part No.**

316L-50DF4-150

**Part Description:**

316L SS Double-Ended DOT-Compliant Sample Cylinder, 1/4 in. FNPT, 150 cm<sup>3</sup>, 5000 psig (344 bar)

## Product Specifications

### General

<b>Body Material</b>	316L Stainless Steel
<b>Connection 1 Size</b>	1/4 in.
<b>Connection 1 Type</b>	Female NPT
<b>Connection 2 Size</b>	1/4 in.
<b>Connection 2 Type</b>	Female NPT
<b>Cylinder volume/info</b>	150 cm <sup>3</sup>
<b>eClass (4.1)</b>	36030101
<b>eClass (6.0)</b>	36-03-01-04
<b>UNSPSC (11.0501)</b>	24111802
<b>UNSPSC (4.03)</b>	24111800
<b>UNSPSC (SWG01)</b>	24111800

**!** The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

**⚠** Caution: Do not mix or interchange valve components with those of other manufacturers.